

HRDP DVR Series

4, 8 & 16 CHANNEL EMBEDDED DIGITAL VIDEO RECORDER

The Performance Series HRDP digital video recorder (DVR) offers a feature set comparable to many high-end embedded DVRs but at a much lower price!

Recording at a rate of up to 120/100 ips NTSC/PAL, HRDP offers high-end capabilities such as a user-friendly front panel, IR remote control, express record configuration, express search, an internal DVD-RW and 2 USB ports for copying evidence. When saving video clips to portable media, a viewer executable is included with each clip, which eliminates the need to install a separate viewer on a PC. HRDP supports continuous, event, and combined continuous/event recording and is configurable per channel. Upon detection of motion, HRDP can automatically boost the ips recording rate to capture additional detail of the scene. E-mail notification can be set up to alert a system administrator of DVR operational status conditions and site status notifications upon detection of motion.

HRDP can be remotely accessed by system administrators and other DVR clients using a PC via Web browser or via the powerful Remote Software included with each HRDP DVR. The Remote Software allows the administrator to configure, update, and operate the DVR from a central location. Remote DVR configuration and downloading software updates from a central site, saves time and money by reducing the need for periodic site visits. System operators can have individual privileges enabled or denied for functions such as live view, playback, backup, and PTZ control.

Market Opportunities

Supporting an advanced feature set and low pricing, the HRDP is an ideal DVR for a wide variety of surveillance applications including small to medium-sized retail, financial, warehouse, and educational facilities. Web browser remote access in addition to Remote Software opens up many new application possibilities for HRDP. Business owners can check in on their businesses from virtually any location using a PC with a Web browser and internet access.

Features

- 4, 8 or 16 looping video inputs
- Continues recording during playback and during transmitting to remote site
- Built-in DVD-RW drive and 2 USB 2.0 ports
- Records up to 120/100 images per second (NTSC/PAL)
- PTZ dome control for a wide variety of protocols
- Remote access through web browser, LAN/WAN (internal NIC), and DSL (remote access software included)
- Self-diagnostics with automatic notification including hard disk drive S.M.A.R.T. protocol
- Multiple search engines (date/time, event, express search)
- Robust MPEG-4 video compression
- Infrared remote control
- Embedded Linux OS — OS embedded in flash



HRDP DVR Series

www.honeywellvideo.com

SPECIFICATIONS


Remote Software	
Sessions Maximum per HRDP recorder	4 simultaneous connections
Administration; configuration, live view, search	1 session
Users viewing live video and retrieving video	2 sessions
Above with PTZ control	1 at time controlling PTZ
Compatibility	Microsoft Windows XP or Vista; See HRDP User Guide for additional detail.
Recorder Unit	
Video Standard	NTSC or PAL
Color Control	Brightness, contrast, saturation and hue
Recording and Transmission Compression Algorithm	MPEG-4
Record Mode	(FIFO) Continuous buffer
Recording Capacity	Hard drive capacities up to 1TB, see ordering section for details
Recording Rate (Global)	120/100 ips (NTSC/PAL)
Video Resolution Settings	CIF: 352x240 (NTSC) or 352x288 (PAL) 2CIF: 704x240 (NTSC) or 704x288 (PAL) 4CIF: 704x480 (NTSC) or 704x576 (PAL)
Video Motion Detection	Configurable zone detection area and sensitivity
Event Recording and Reporting	Input via – alarm i/p contacts, and motion. Reporting via alarm o/p contacts, e-mail notification
Removable Media	Built-in DVD-RW and two USB ports
Still Image	JPG file format using RAS
Front Panel Control	Intuitive operation supports IR remote control
NTP Client	Synchronize timing to NTP servers
DHCP Enabled	DHCP or static IP entry
Port Number Setup	Individual entries for remote port and web port
PTZ Protocols Support	Support for up to 60 PTZ protocols
Language Support	English, French, Italian, Spanish, Portuguese, German, Korean, and Russian

Connections	
Video Input	4, 8, or 16 – Looping, BNC 1 Vp-p @ 75 Ohms, Auto Terminating
Video Output	1 – Composite, BNC 1 Vp-p @ 75 Ohms (4, 8, 16 ch) 1 - VGA (4, 8, 16 ch) 1 - S-Video Main Monitor (16 ch only) 3 – Spot (16 ch only) BNC 1.0 – Vp-p @ 75 Ohms 1 – Spot (4 & 8 ch only) BNC 1.0 – Vp-p @ 75 Ohms
Audio Input/Output	1 – Line level, RCA G.726 Compression 1 – Line Out, RCA
Sensor Inputs General Purpose	NO/NC settable 4 – 4 ch DVR 8 – 8 ch DVR 16 – 16 ch DVR
Control Outputs	1 NC or NO, 4 & 8 ch DVR 24V, 1 A 4 NC or NO, 16 ch DVR 24V, 1A
Serial Ports	1 – RS232-C DB9 (P) 2 – USB (2.0) 1 – RS485 port
Internal Storage	EIDE HDD
Networking	10/100 base Ethernet (RJ-45)
Electrical	
Input Voltage	110 ~ 230 VAC, 1.75 ~ 0.85 A, 47-63 Hz
Power Consumption	153 Watts
Mechanical	
Dimensions (W x H x D)	15.75"(W) x 15.75"(D) x 3.5"(H) 400 mm x 400 mm x 88 mm
Weight	Unit: 18 lb (8.2 kg) Shipping: 22 lbs (10 kg)
Construction	Housing: Steel chassis Finish: Black matte paint
Environmental	
Temperature	Operating: 32°F to 104°F (0°C to 40°C) Storage: 32°F to 104°F (0°C to 40°C)
Relative Humidity	0% - 90%, non-condensing
Regulatory	
Emissions	FCC: Part 15 Subpart B, Class A EN55022:(1994+A1):(1995+A2):(1997[ClassA]) EN61000-3-3: (1995+A1):(2001) EN61000-3-2: (2000)
Immunity	EN50130-4:1995 + A1:1988
Safety	UL/cUL 60950-1 First Edition October 31, 2007 IEC 60950-1:2001 First Edition

HRDP DVR Series

www.honeywellvideo.com

SYSTEM DRAWING




HRDP DVR Series

www.honeywellvideo.com


ACCESSORIES, DIMENSIONS, ORDERING

Recommended Accessories		Recommended Accessories, Cont.	
HRDP DVR		Cameras*	
HRDPRC	Spare IR Remote Control	HB73	IR Bullet, super high resolution True Day/Night
HRDPRMKT	19-inch Rack Mount Kit	HD73	Mini-dome, super high resolution day/night
Monitors*		HD3CH	Mini-dome, super high resolution day/night vandal resistant
HMC14HRX	14" Color CRT Monitor	ACUIX™	High-performance PTZ camera
HMC14HRRK1X	Rack Mount Kit for HMC14HRX Monitor	Surge Protection	
HMLCD19e2	19" e-Series Color LCD Monitor (VGA)	HCSP1	Camera Surge Protector
HMLCD17L	17" L-Series Color LCD Monitor (VGA)	HDSP1	PTZ Dome Surge Protector

* See Honeywell's full line of monitors and cameras at www.honeywellvideo.com



Front View



Side View

Ordering

HRDP16 D 1000 X

Signal Format

X PAL
NTSC

Storage 1000 GB Fixed IDE HDD**
750 GB*
500 GB
250 GB

DVD-RW D = Internal DVD-RW drive

Model

HRDP16 16 channel DVR
HRDP8 8 channel DVR
HRDP4 4 channel DVR

** Only available with 16 ch DVR

* Only available with 8 & 16 ch DVR

Honeywell Security & Data Collection

Honeywell
2700 Blankenbaker Pkwy, Suite 150
Louisville, KY 40299
1.800.796.2288 (CCTV)
www.honeywell.com

L/HRDP/D
September 2008
© 2008 Honeywell International Inc.

Honeywell